Product fiche concerning the COMMISSION DELEGATED REGULATIONS

(EU) No 811/2013 of 18 February 2013 (EU) No 813/2013 of 2 August 2013

Oil Boilers

		1	1		T		
Pro Range: Vortex Outdoor Module	Symbols	Unit	15-21	15-26	26-36	36-46	
Condensing boiler			Yes	Yes	Yes	Yes	
Low temperature boiler			No	No	No	No	
B1 Boiler			No	No	No	No	
Combination heater			No	No	No	No	
Rated heat output	Prated	kW	21	26	36	46	
Useful heat output							
At rated heat output and high temp regime	P ₄	kW	21	26	36	46	
At 30% of rated heat output and low temp regime	P ₁	kW	6.3	7.8	10.8	13.8	
Auxiliary electricity consumption							
At Full load	Elmax	kW	0.158	0.130	0.150	0.148	
At part load	Elmin	kW	0.052	0.039	0.049	0.052	
In standby mode	P_{SB}	kW	0	0	0	0	
Useful efficiency							
Seasonal space heating energy efficiency	ηs	%	90.81	91.71	94.56	90.00	
At rated heat output and high temperature regime	η_4	%	88.9	93.6	95.1	90.8	
At 30% of rated heat output and low temperature regime	$\eta_{\scriptscriptstyle 1}$	%	97.1	96.4	99.3	94.4	
Other items							
Standby heat loss	P _{stby}	kW	0.23	0.264	0.293	0.301	
Ignition burner power consumption	P_{ign}	kW	0	0	0	0	
Annual energy consumption	Q _{HE}	kWh	-	-	-	-	
Sound power level, indoors	L _{WA}	db	49.6	50.6	53.7	51.1	
Emissions of nitrogen oxides	NOx	mg/ kWh	180.4	151.8	127.3	132.8	
Emissions Class	<u> </u>		2	2	2	2	
Daily fuel consumption	Q _{fuel}	kWh	-	-	-	-	
Annual fuel consumption	AFC	GJ	-	-	-	-	

Grant Engineering (UK) Ltd

Hopton House, Hopton Industrial Estate, Devizes, Wiltshire, SN10 2EU t: +44 (0)1380 736920 f: +44 (0)1380 736991 e: info@grantuk.com w: www.grantuk.com



Pro Range: Vortex Pro External	Symbols	Unit	46-58	28-70			
Condensing boiler			Yes	Yes			
Low temperature boiler			No	No			
B1 Boiler			No	No			
Combination heater			No	No			
Rated heat output	Prated	kW	58	70			
Useful heat output							
At rated heat output and high temp regime	P_4	kW	58	70			
At 30% of rated heat output and low temp regime	P ₁	kW	17.4	21			
Auxiliary electricity consumption							
At Full load	Elmax	kW	0.189	0.182			
At part load	Elmin	kW	0.072	0.075			
In standby mode	P_{SB}	kW	0	0			
Useful efficiency							
Seasonal space heating energy efficiency	ηs	%	91.94	91.61			
At rated heat output and high temperature regime	$\eta_{\scriptscriptstyle 4}$	%	91.5	90.9			
At 30% of rated heat output and low temperature regime	η_1	%	96.7	96.2			
Other items							
Standby heat loss	P _{stby}	kW	0.309	0.306			
Ignition burner power consumption	P _{ign}	kW	0	0			
Annual energy consumption	Q_{HE}	kWh	-	-			
Sound power level, indoors	L _{WA}	db	55.7	55.0			
Emissions of nitrogen oxides	NOx	mg/ kWh	106.9	98			
Emissions Class		<u> </u>	3	3			
Daily fuel consumption	Q _{fuel}	kWh	-	-			
Annual fuel consumption	AFC	GJ	-	-			



	<u> </u>				Ī			I	I	<u> </u>	
Pro range: Vortex Utility	Symbols	Unit	15-21	15-26 Kitchen Boiler	26-36 Utility Boiler	36/46	46-58	58-70	System 15-26S	26-36-S Utility System Boiler	System 36-46S
Condensing boiler			Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Low temperature boiler			No	No	No	No	No	No	No	No	No
B1 Boiler			No	No	No	No	No	No	No	No	No
Combination heater			No	No	No	No	No	No	No	No	No
Rated heat output	Prated	kW	21	26	36	46	58	70	26	36	46
Useful heat output		•			•		•	•	•	•	
At rated heat output and high temp regime	P_4	kW	21	26	36	46	58	70	26	36	46
At 30% of rated heat output and low temp regime	P ₁	kW	6.3	7.8	10.8	13.8	17.4	21	7.8	10.8	13.8
Auxiliary electricity consumption	on										
At Full load	elmax	kW	0.158	0.130	0.150	0.148	0.189	0.182	0.130	0.150	0.148
At part load	elmin	kW	0.052	0.039	0.049	0.052	0.072	0.075	0.039	0.049	0.052
In standby mode	P_{SB}	kW	0	0	0	0	0	0	0	0	0
Useful efficiency											
Seasonal space heating energy efficiency	ηѕ	%	90.81	91.71	94.56	90.00	91.94	91.61	91.71	94.56	90.00
At rated heat output and high temperature regime	$\eta_{\scriptscriptstyle 4}$	%	88.9	93.6	95.1	90.8	91.5	90.9	93.6	95.1	90.8
At 30% of rated heat output and low temperature regime	$\eta_{\scriptscriptstyle 1}$	%	97.1	96.4	99.3	94.4	96.7	96.2	96.4	99.3	94.4
Other items											
Standby heat loss	P _{stby}	kW	0.23	0.264	0.293	0.301	0.309	0.306	0.264	0.293	0.301
Ignition burner power consumption	P _{ign}	kW	0	0	0	0	0	0	0	0	0
Annual energy consumption	Q_{HE}	kWh	-	-	-	-	-	-	-	-	-
Sound power level, indoors	L _{WA}	db	49.6	50.6	53.7	51.1	55.7	55.0	50.6	53.7	51.1
Emissions of nitrogen oxides	NOx	mg/ kWh	180.4	151.8	127.3	132.8	106.9	98	151.8	127.3	132.8
Emissions Class			2	2	2	2	3	3	2	2	2
Daily fuel consumption	Q _{fuel}	kWh	-	-	-	-	-	-	-	-	-
Annual fuel consumption	AFC	GJ	ı	-	-	-	-	-	-	-	-



			<u> </u>	<u> </u>	
Pro Range: Vortex Condensing Combi	Symbols	Unit	21	26	36
Condensing boiler			Yes	Yes	Yes
Low temperature boiler			No	No	No
B1 Boiler			No	No	No
Combination heater			Yes	Yes	Yes
Rated heat output	Prated	kW	21	26	36
Useful heat output	•	•			
At rated heat output and high temperature regime	P ₄	kW	21	26	36
At 30% of rated heat output and low temperature regime	P ₁	kW	6.3	7.8	10.8
Auxiliary electricity consumption			1	1	Т
At Full load	elmax	kW	0.158	0.13	0.15
At part load	elmin	kW	0.052	0.052	0.039
In standby mode	P_{SB}	kW	0.009	0.009	0.009
Declared load profile			XL	XL	XL
Daily electricity consumption	Q _{elec}		0.293	0.23	0.205
Annual electricity consumption	AEC		65.4	50.5	45.2
Useful efficiency					
Seasonal space heating energy efficiency	ηs	%	90.81	91.71	94.56
At rated heat output and high temperature regime	η_4	%	88.9	93.6	95.1
At 30% of rated heat output and low temperature regime	η_1	%	97.1	96.4	99.3
Other items			ı	ı	
Standby heat loss	P _{stby}	kW	0.23	0.264	0.522
Ignition burner power consumption	P _{ign}	kW	0	0	0
Annual energy consumption	Q_{HE}	kWh	-	-	-
Sound power level, indoors	L_{WA}	dB	50.6	50.6	53.7
Emissions of nitrogen oxides	NOx	mg/ kWh	180.4	151.8	127.3
Emissions Class			2	2	2
Water heating efficiency	$\eta_{\scriptscriptstyle wh}$	%	68.23	62.6	60.38
Daily fuel consumption	Q _{fuel}	kWh	27.2	30	31.1
Annual fuel consumption	AFC	GJ	21.556	26.673	24.67



Vortex Boiler House	Symbols	Unit	Boilerhouse 15/21	Boilerhouse 21/26	Boilerhouse 26/35	Boilerhouse 36-46	Boilerhouse 46-58	Boilerhouse 58-70
Condensing boiler			Yes	Yes	Yes	Yes	Yes	Yes
Low temperature boiler			No	No	No	No	No	No
B1 Boiler			No	No	No	No	No	No
Combination heater			No	No	No	No	No	No
Rated heat output	P _{rated}	kW	21	26	35	46	58	70
Useful heat output								
At rated heat output and high temperature regime	P_4	kW	21	26	35	46	58	70
At 30% of rated heat output and low temperature regime	P ₁	kW	5.8	7.4	9.6	13.8	17.4	21
Auxiliary electricity consumption								
At Full load	elmax	kW	0.113	0.154	0.146	0.155	0.215	0.215
At part load	elmin	kW	0.035	0.047	0.045	0.046	0.064	0.064
In standby mode	P_{SB}	kW	0	0	0	0	0	0
Useful efficiency								
Seasonal space heating energy efficiency	ηs	%	92.70	91.70	92.40	90.06	91.98	91.66
At rated heat output and high temperature regime	η_4	%	92.2	92.4	92.4	90.8	91.5	90.9
At 30% of rated heat output and low temperature regime	η_1	%	98.4	97.2	97.5	94.4	96.7	96.2
Other items		t	+		1			_
Standby heat loss	P _{stby}	kW	0.082	0.091	0.09	0.1	0.12	0.12
Ignition burner power consumption	P _{ign}	kW	0	0	0	0	0	0
Annual energy consumption	Q_{HE}	kWh	-	-	-	-	-	-
Sound power level, indoors	L_{WA}	dB	63	63	66	61	68	67
Emissions of nitrogen oxides	NOx	mg/ kWh	176	168	166	132.8	106.9	98
Emissions Class			2	2	2	2	3	3
Daily fuel consumption	Q _{fuel}	kWh	-	-	-	-	-	-
Annual fuel consumption	AFC	GJ	-	-	-	-	-	-



Pro Range: Vortex Outdoor Condensing Combi Condensing boiler Low temperature boiler B1 Boiler	Symbols	Onit	S Vortex Outdoor S Combi 21	Yes No	g Yes No
Combination heater			Yes	Yes	Yes
Rated heat output	Prated	kW	21	26	36
Useful heat output	774104	IXVV	21		00
At rated heat output and high temperature regime At 30% of rated heat output and low	P ₄	kW	21	26	36
temperature regime	P ₁	kW	6.3	7.8	10.8
Auxiliary electricity consumption	T	1	Г	 	Т
At Full load	elmax	kW	0.158	0.13	0.15
At part load	elmin	kW	0.052	0.052	0.039
In standby mode	P_{SB}	kW	0.009	0.009	0.009
Declared load profile			XL	XL	XL
Daily electricity consumption	Q _{elec}		0.293	0.23	0.205
Annual electricity consumption	AEC		65.4	50.5	45.2
Useful efficiency					
Seasonal space heating energy efficiency	ηѕ	%	90.81	91.71	94.56
At rated heat output and high temperature regime	η_4	%	88.9	93.6	95.1
At 30% of rated heat output and low temperature regime	η_1	%	97.1	96.4	99.3
Other items	1	T	Π	I	T.
Standby heat loss	P _{stby}	kW	0.23	0.264	0.522
Ignition burner power consumption	P _{ign}	kW	0	0	0
Annual energy consumption	Q_{HE}	kWh	-	-	-
Sound power level, indoors	L_{WA}	dB	50.6	50.6	53.7
Emissions of nitrogen oxides	NOx	mg/ kWh	180.4	151.8	127.3
Emissions Class			2	2	2
Water heating efficiency	η_{wh}	%	68.23	62.6	60.38
Daily fuel consumption	Q _{fuel}	kWh	30	30	31.1
Annual fuel consumption	AFC	GJ	21.556	26.673	24.67



		l	l
Pro Range:			
Vortex Pro Combi XS	Symbols	Unit	26
Condensing boiler			Yes
Low temperature boiler			No
B1 Boiler			No
Combination heater			Yes
Rated heat output	Prated	kW	26
Useful heat output			
At rated heat output and high temperature regime	P_4	kW	26
At 30% of rated heat output and low temperature regime	P_1	kW	8.3
Auxiliary electricity consumption		•	
At Full load	elmax	kW	0.167
At part load	elmin	kW	0.049
In standby mode	P _{SB}	kW	0.001
Declared load profile			XL
Daily electricity consumption	Q _{elec}		0.269
Annual electricity consumption	AEC		59.2
Useful efficiency			
Seasonal space heating energy efficiency	ηѕ	%	92.00
At rated heat output and high temperature regime	η_4	%	91.92
At 30% of rated heat output and low temperature regime	η_1	%	97.64
Other items		T	Π
Standby heat loss	P _{stby}	kW	0.135
Ignition burner power consumption	P _{ign}	kW	0
Annual energy consumption	Q _{HE}	kWh	-
Sound power level, indoors	L _{WA}	dB	49.6
Emissions of nitrogen oxides	NOx	mg/ kWh	162
Emissions Class			2
Water heating efficiency	η_{wh}	%	68.11
Daily fuel consumption	Q_{fuel}	kWh	27.3
Annual fuel consumption	AFC	GJ	21.6



			I	I	I	1	1	
Eco Range:						5-21	1-26	5-35
Vortex Eco Utility	<u>s</u>					SYSTEM 15-21	SYSTEM 21-26	SYSTEM 26-35
	Symbols	 	15-21	21-26	26-35	/STE	STE	/STE
	· σ	Unit	15	21	26	S	်	Ś
Condensing boiler			Yes	Yes	Yes	Yes	Yes	Yes
Low temperature boiler			No	No	No	No	No	No
B1 Boiler			No	No	No	No	No	No
Combination heater			No	No	No	No	No	No
Rated heat output	P _{rated}	kW	21	26	35	21	26	35
Useful heat output	·							
At rated heat output and high temperature regime	P_4	kW	21	26	35	21	26	35
At 30% of rated heat output and low temperature regime	P ₁	kW	5.8	7.4	9.6	5.8	7.4	9.6
Auxiliary electricity consumption								
At Full load	elmax	kW	0.113	0.154	0.146	0.113	0.154	0.146
At part load	elmin	kW	0.035	0.047	0.045	0.035	0.047	0.045
In standby mode	P_{SB}	kW	0	0	0	0	0	0
Useful efficiency		•			•			
Seasonal space heating energy efficiency	Ŋs	%	92.7	91.7	92.4	92.7	91.7	92.4
At rated heat output and high temperature regime	η_4	%	92.2	92.4	92.4	92.2	92.4	92.4
At 30% of rated heat output and low temperature regime	η_1	%	98.4	97.2	97.5	98.4	97.2	97.5
Other items								
Standby heat loss	P _{stby}	kW	0.082	0.091	0.09	0.082	0.091	0.09
Ignition burner power consumption	P _{ign}	kW	0	0	0	0	0	0
Annual energy consumption	Q _{HE}	kWh	-	-	-	-	-	-
Sound power level, indoors	L _{WA}	dB	50.6	50.6	53.7	50.6	50.6	53.7
Emissions of nitrogen oxides	NOx	mg/ kWh	176	168	166	176	168	166
Emissions Class			2	2	2	2	2	2
Daily fuel consumption	Q _{fuel}	kWh	-	-	-	-	-	-
Annual fuel consumption	AFC	GJ	-	-	-	-	-	-
	•	•	•			•		



								1
Eco Range: Vortex Eco External	Symbols	Unit	15-21	21-26	26-35	SYSTEM 15-21	SYSTEM 21-26	SYSTEM 26-35
Condensing boiler			Yes	Yes	Yes	Yes	Yes	Yes
Low temperature boiler			No	No	No	No	No	No
B1 Boiler			No	No	No	No	No	No
Combination heater			No	No	No	No	No	No
Rated heat output	P _{rated}	kW	21	26	35	21	26	35
Useful heat output				•				
At rated heat output and high temperature regime	P_4	kW	21	26	35	21	26	35
At 30% of rated heat output and low temperature regime	P_1	kW	5.8	7.4	9.6	5.8	7.4	9.6
Auxiliary electricity consumption								
At Full load	elmax	kW	0.113	0.154	0.146	0.113	0.154	0.146
At Part load	elmin	kW	0.035	0.047	0.045	0.035	0.047	0.045
In standby mode	P_{SB}	kW	0	0	0	0	0	0
Useful efficiency								
Seasonal space heating energy efficiency	Ŋs	%	92.7	91.7	92.4	92.7	91.7	92.4
At rated heat output and high temperature regime	η_4	%	92.2	92.4	92.4	92.2	92.4	92.4
At 30% of rated heat output and low temperature regime	η_1	%	98.4	97.2	97.5	98.4	97.2	97.5
Other items		T						
Standby heat loss	P _{stby}	kW	0.082	0.091	0.09	0.082	0.091	0.09
Ignition burner power consumption	P _{ign}	kW	0	0	0	0	0	0
Annual energy consumption	Q _{HE}	kWh	-	-	-	-	-	-
Sound power level, indoors	L _{WA}	dB	50.6	50.6	53.7	50.6	50.6	53.7
Emissions of nitrogen oxides	NOx	mg/ kWh	176	168	166	176	168	166
Emissions Class			2	2	2	2	2	2
Daily fuel consumption	Q _{fuel}	kWh	-	-	-	-	-	-
Annual fuel consumption	AFC	GJ						



Eco Range: Vortex Eco Wall Hung	Symbols	Unit	12-16	16-21	SYSTEM 12-16	SYSTEM 16-21
Condensing boiler			Yes	Yes	Yes	Yes
Low temperature boiler			No	No	No	No
B1 Boiler			No	No	No	No
Combination heater			No	No	No	No
Rated heat output	P _{rated}	kW	16	21	16	21
Useful heat output	J	l	I.	I.		
At rated heat output and high temperature regime	P_4	kW	16	21	16	21
At 30% of rated heat output and low temperature regime	P ₁	kW	4.8	6.3	4.8	6.3
Auxiliary electricity con	nsumptio	on				
At Full load	elmax	kW	0.164	0.150	0.164	0.150
At part load	elmin	kW	0.062	0.07	0.062	0.07
In standby mode	P_{SB}	kW	0	0	0	0
Useful efficiency						
Seasonal space heating energy efficiency	Ŋs	%	90.13	90.52	90.13	90.52
At rated heat output and high temperature regime	η ₄	%	93.1	90.8	93.1	90.8
At 30% of rated heat output and low temperature regime	η_1	%	96.7	96.9	96.7	96.9
Other items						
Standby heat loss	P _{stby}	kW	0.207	0.236	0.207	0.236
Ignition burner power consumption	P _{ign}	kW	0	0	0	0
Annual energy consumption	Q _{HE}	kWh	-	-	-	-
Sound power level, indoors	L _{WA}	dB	51.2	51.7	51.2	51.7
Emissions of nitrogen oxides	NOx	mg/ kWh	147	149	147	149
Emissions Class			2	2	2	2
Daily fuel consumption	Q _{fuel}	kWh		-	-	_
Annual fuel consumption	AFC	GJ	-	_	-	-



Eco Range:						
Vortex Eco Wall Hung External	Symbols	Unit	12-16	16-21	SYSTEM 12-16	SYSTEM 16-21
Condensing boiler			Yes	Yes	Yes	Yes
Low temperature boiler			No	No	No	No
B1 Boiler			No	No	No	No
Combination heater			No	No	No	No
Rated heat output	P _{rated}	kW	16	21	16	21
Useful heat output	I.	I.	I	I	I	I
At rated heat output and high temperature regime	P_4	kW	16	21	16	21
At 30% of rated heat output and low temperature regime	P ₁	kW	4.8	6.3	4.8	6.3
Auxiliary electricity con	nsumptio	on				
At Full load	elmax	kW	0.164	0.150	0.164	0.150
At part load	elmin	kW	0.062	0.07	0.062	0.07
In standby mode	P_{SB}	kW	0	0	0	0
Useful efficiency						
Seasonal space heating energy efficiency	Ŋs	%	90.13	90.52	90.13	90.52
At rated heat output and high temperature regime	η ₄	%	93.1	90.8	93.1	90.8
At 30% of rated heat output and low temperature regime	η_1	%	96.7	96.9	96.7	96.9
Other items						
Standby heat loss	P _{stby}	kW	0.207	0.236	0.207	0.236
Ignition burner power consumption	P _{ign}	kW	0	0	0	0
Annual energy consumption	Q _{HE}	kWh	-	-	-	-
Sound power level, indoors	L _{WA}	dB	51.2	51.7	51.2	51.7
Emissions of nitrogen oxides	NOx	mg/ kWh	147	149	147	149
Emissions Class			2	2	2	2
Daily fuel consumption	Q _{fuel}	kWh	-	-	-	-
Annual fuel consumption	AFC	GJ	-	-	-	-



End of Life Information

General

Grant oil boilers incorporate components manufactured from a variety of different materials. The majority of these materials can be recycled whilst the smaller remainder cannot. Materials that cannot be recycled must be disposed of according to local regulations using appropriate waste collection and/or disposal services.

Disassembly

There is little risk to those involved in the disassembly of this product. Please refer to and follow the Health and Safety Information given in the Installation & Servicing Instructions provided with the boiler.

For guidance on the disassembly of the boiler refer to the information given in the Servicing section of the Installation & Servicing Instructions provided with the boiler.

Recycling

Many of the materials used in Grant oil boilers can be recycled, these are listed in the table below:

Component	Material
Outer casing panels	Mild steel (polyester powder coated)
Primary heat exchanger and baffles	Mild steel
Secondary heat exchanger	Stainless steel
Secondary heat exchanger spirals	Aluminium alloy
Pipework	Copper
Burner body/flange	Aluminium alloy
Burner oil pump	Aluminium alloy/steel
Riello oil burner cover	Plastic
Electrical wiring	Copper/plastic
Thermostats	Copper/plastic
Printed Circuit boards	Copper/plastic

Disposal

All materials other than those listed above must be disposed of responsibly as general waste.

Grant Oil Boiler Fiche. V2.1 07/03/2018

Neil Sawers Technical Manager

